



General use



## Стоманени въжета ROPETEX S49

### Информация за продукта

**ROPETEX**



ROPETEX S49 is a wire rope for general purposes like hanging signs, control and signaling devices, but not for lifting. It's most used in small diameters up to 6 mm. ROPETEX S49 is equipped with a Steel Core (WSC).

ROPETEX S42 is the same rope but has a Fibre Core (FC) and is therefore more flexible.

**Структура:** 6x7-WSC (7x7)

**Маркировка:** Съгласно релевантния стандарт

**Работна температура:** -40°C до +200°C, за работни температури между 100°C и 200°C намалете MBF с минус 10 %.

**Стандарт:** EN 12385-4

**Предупреждение:** Да не се използва за повдигане

**Коефициент на запълване:** 0,55

Продуктов номер	Диаметър на въжето мм	Метална зона мм <sup>2</sup>	Мин. разкъсващо усилие кN 1960 N/mm <sup>2</sup>	Тегло кг/100м
101100104270040	1	0,43	0.76	0,38
101100154270040	1,5	0,97	1.71	0,86
101100204270040	2	1,73	3.04	1,54
101100244270040	2,4	-	4.38	2,2
101100254270040	2,5	2,7	4.75	2,4
101100304270040	3	3,89	6.84	3,46
101100404270040	4	6,91	12.2	6,14
101100604270040	6	15,6	27.4	14