

## Ropetex Perform 6C

### Product information

**ROPETEX**



**Standard:** EN 12385-4

**ISO 4309 Rope Category No:** 10-40mm RCN.09

**Rope construction:** 6x36-IWRC, Compacted outer strands

**Marking:** According to standard

**Standard:** EN 12385-4

**Fill factor:** 0,64

**RCN:** 09

Winch rope



Tower crane



Container crane



Mobile port crane



Offshore crane



Loading crane




Crawler crane



Piling crane



Overhead cranes



Part Code	Rope Diameter, mm	Steel area mm <sup>2</sup>	Min. Breaking force kN. 1960 N/mm <sup>2</sup>	Min. Breaking force kN. 2160 N/mm <sup>2</sup>	Weight kg/100m
01.G12X06100G	10	50.3	84.2	89.6	45
01.G12X06120G	12	72.5	118	126	65
01.G12X06130G	13	85	138	147	76
01.G12X06140G	14	96.6	169	179	89
01.G12X06160G	16	129	210	224	116
01.G12X06180G	18	163	266	283	147
01.G12X06190G	19	182	299	319	164
01.G12X06200G	20	201	328	349	182
01.G12X06220G	22	244	397	424	220
01.G12X06240G	24	290	473	504	262
01.G12X06250G	25	315	513	547	284
01.G12X06260G	26	340	555	592	307
01.G12X06280G	28	395	643	686	356
01.G12X06300G	30	453	739	788	409
01.G12X06320G	32	515	840	897	465
01.G12X06340G	34	582	949	1010	525
01.G12X06350G	35	616	1010	1069	557
01.G12X06360G	36	652	1069	1138	589
01.G12X06380G	38	727	1187	1265	656
01.G12X06400G	40	805	1314	1402	727