


## Ropetex 55

### Product information



**ROPETEX**



Excellent Resistance to Rotation giving over three times more lifting height than a conventional 18 x 7 class rope. Flexibility is optimised by the unique strand and rope construction. Langs Lay construction combines excellent wear characteristics with efficient spooling on the drum.

RopeTex Ropes are lubricated with the very latest High Performance Wire rope lubricants to give excellent corrosion protection, fatigue life combined with low fling off

**ISO 4309 Rope Category No:** All Diameters **RCN.23-1**

**Features:** Very High Breaking Load

**Material:** High Carbon Steel

**Marking:** According to standard

**Finish:** Galvanised as standard

**Standard:** EN 12385-4

**Fill factor:** 0,64

**RCN:** 23-1

Part Code	Rope Diameter,	Min. Breaking force kN. 2160 N/mm <sup>2</sup>	Breaking Load ton	Weight kg/100m
01.G35X55080H	8	50.5	5.15	27.6
01.G35X55090H	9	64	6.52	34.4
01.G35X55100H	10	79	8.05	43
01.G35X55110H	11	95.6	9.75	52
01.G35X55120H	12	114	11.62	62
01.G35X55130H	13	134	13.66	72
01.G35X55140H	14	155	15.8	84
01.G35X55150H	15	178	18.14	96
01.G35X55160H	16	202	20.6	110
01.G35X55170H	17	228	23.2	120
01.G35X55180H	18	256	26.1	135
01.G35X55190H	19	285	29.1	150
01.G35X55200H	20	316	32.2	166
01.G35X55220H	22	382	38.94	201
01.G35X55240H	24	455	46.38	245
01.G35X55260H	26	527	53.72	297
01.G35X55280H	28	612	62.38	345