

Geared Trolley TSG KITO



Product information

General: Geared trolley with capacity from 0,125 tons up to 5 tons. The standard trolley includes rubber bumper, safety lug and suspender.

Material: Pressed steel plate.

Marking: According to standard, CE-marked

Temperature range: -40°C up to +60°C (-20°C up to + 40°C for the use with a electric chain hoist)

Standard: EN 13157

Safety factor: 4:1

Part Code	WLL ton	Beam width mm	Model	Chain length m
16.05TSG001SC030	0.125	58-163	Standard	3
16.05TSG0012C030	0.125	164-305	W30	3
16.05TSG002SC030	0.25	58-163	Standard	3
16.05TSG0032C030	0.25	164-305	W30	3
16.05TSG005SC030	0.5	58-163	Standard	3
16.05TSG0052C030	0.5	164-305	W30	3
16.05TSG010SC030	1	58-163	Standard	3
16.05TSG0102C030	1	164-305	W30	3

16.05TSG015SC030	1.5	82-204	Standard	3
16.05TSG0152C030	1.5	205-305	W30	3
16.05TSG020SC030	2	82-204	Standard	3
16.05TSG0202C030	2	205-305	W30	3
16.05TSG025SC030	2.5	82-204	Standard	3
16.05TSG0252C030	2.5	205-305	W30	3
16.05TSG030SC030	3	82-204	Standard	3
16.05TSG0302C030	3	205-305	W30	3
16.05TSG050SC030	5	100-204	Standard	3.5
16.05TSG0502C030	5	205-305	W30	3,5
16.05TSG075SC030	7.5	150-220	Standard	3.5
16.05TSG0752C030	7.5	221-305	W30	3,5
16.05TSG100SC030	10	150-220	Standard	4
16.05TSG1002C030	10	221-305	W30	4,0
16.05TSG150SC030	15	150-220	Standard	4.5
16.05TSG1502C030	15	221-305	W30	4.5
16.05TSG200SC030	20	150-220	Standard	4.5
16.05TSG2002C030	20	221-305	W30	4.5
16.05TSG300SC030	30	190	Standard	4.5
16.05TSG3002C030	30	191-305	W30	4.5