



Horizontal Lifting Clamp FHX/FHSX

Product information

For horizontal lifting and transporting of steel plates and other non-deflecting materials. FHX/FHSX lifting clamps only to be used and sold in pairs (or multiple pairs).

Model FHX: Standard clamp

Model FHSX: Clamp with enlarged jaw opening.

- Compact design and high lifting capacity
- Lightweight design for easy handling
- Tough quality heavy duty welded body

Marking: According to standard, CE-marked, Type, serial number, WLL, Jaw opening.

Temperature range: - 40°C up to +100°C.

Standard: EN 13155

Note: Must always be used in pairs (or multiple pairs)

Warning: Hardness level of the material surface may not exceed 37 Hrc (345 Hb, 1166 N/mm²)

Part Code	Code	WLL ton	Jaw width mm	V mm	S mm	W mm	T mm	H mm	X mm	U mm	Y mm	Weight kg
16.01953100	1 FHX	1	0-35	140	99	10	25	11.5	65	188	15	2.6
16.01953200	2 FHX	2	0-60	180	118	15	30.5	19.5	90	287	16	7
16.01954200	2 FHSX	2	0-100	180	120	15	30.5	19.5	90	383	15	9.2
16.01953300	3 FHX	3	0-60	180	118	20	30.5	19.5	90	291	16	8
16.01954300	3 FHSX	3	0-100	180	120	20	30.5	19.5	90	387	15	10
16.01953400	4 FHX	4	0-60	220	145	25	30.5	19.5	105	304	20	13
16.01954400	4 FHSX	4	0-100	220	145	25	30.5	19.5	105	414	20	15
16.01953600	6 FHX	6	0-60	220	145	25	30.5	19.5	110	307	20	14
16.01954600	6 FHSX	6	0-100	220	145	25	30.5	19.5	120	414	20	16.5
16.01953800	8 FHX	8	0-60	225	135	35	30.5	19.5	120	336	30	19
16.01954800	8 FHSX	8	0-100	225	135	35	30.5	19.5	120	428	30	21
16.01953010	10 FHX	10	0-60	225	135	35	30.5	19.5	120	336	30	19
16.01954010	10 FHSX	10	0-100	225	135	35	30.5	19.5	120	428	30	22
16.01953012	12 FHX	12	0-60	225	135	35	30.5	19.5	120	336	30	19
16.01954012	12 FHSX	12	0-100	225	135	35	30.5	19.5	120	428	30	22
16.01953015	15 FHX	15	0-60	262	147	35	43	21.5	160	344	35	30
16.01853820	15 FHSX	15	0-150	350	240	35	45	27.5	140	665	35	53
16.01953025	25 FHX	25	0-60	262	147	40	43	21.5	175	349	35	33

Blueprint

