

Pipe Lifting TBC - TBC-A



Product information

Lightweight clamp with pressure resistant plastic cam for vertical concrete pipe lifting

Application

- For vertical lifting and transporting of concrete pipes and wells
- Terrier TBC / TBC-A lifting clamps must always be used in pairs (or per three clamps)
- TBC jaw opening available from: 60 to 120 mm
- TBC-A has an extra large jaw opening available from: 50 to 220 mm (adjustable in steps of 25 mm)
- Working load limit (WLL) 1000kg
- Other jaw openings available upon request

Features and benefits

- The cam is covered with a special high quality pressure resistant plastic
- Maintenance-friendly clamp, plastic pressure resistant cover is easy to change
- Tough quality welded body
- Lightweight design for easy handling

Marking: According to standard, CE-marked

Temperature range: -40°C up to 50°C

Standard: EN 13155

| Code | WLL ton | Beam width mm mm | Jaw width mm | S mm | T mm | U mm | W mm | X mm | Y mm | Z mm |
|---------|------------|------------------------|-----------------|---------|---------|---------|---------|---------|---------|---------|
| 1 TBC | 1 | 60-120 | 60-120 | 169 | 12 | 326 | 97 | 60 | 12 | 40 |
| 1 TBC-A | 1 | 50-220 | 50-220 | 262 | 12 | 459 | 106 | 60 | 12 | 40 |

Blueprint

