

Vertical Lifting Clamp TBLC - Non marking



Product information

Clamp for vertical lifting and transporting of all plates, blocks and structures with parallel sides without marking, scratching and or damaging the material surface. Perfect for lifting materials such as (stainless) steel, aluminum, nature stone, composite, painted materials, wood, glass, plastic, etc. The clamp is locked in the open position. To perform lifting, the operator must activate the handle and hold it up while the force on the lifting eye is going upwards. When laying down the load, the clamp automatically locks itself open.

Features:

- 2 special synthetic anti-friction pads to guarantee non-marking.
- Lightweight design and easy to use.
- Tough quality heavy duty body.
- Maintenance-friendly, easy to exchange parts. Parts available upon request.
- No minimal WLL needed.

Marking: According to standard, CE-marked

Temperature range: -10°C to +30°C.

Standard: EN 13155

Part Code	Code	WLL ton	Jaw width mm	V min-max	U min-max	S mm	T mm	X mm	Y mm	Weight kg
16.86801005	0.5 TBLC	0.5	30-110	270 - 325	305-460	95	45	80*70	15	7
16.86801010	1 TBLC	1	100-230	425 - 530	380-655	120	45	80*70	15	12.3
16.86801020	2 TBLC	2	220-360	580 - 675	410-735	140	45	80*70	15	18
16.86801030	3 TBLC	3	350-500	725 - 835	530 - 900	178	64	100*90	16	33

Blueprint

