



Push trolley

Product information

Push trolley for IPE and T beams. The wheels are equipped with duration lubricated ball bearings. The hoist or lifter can be attached directly to the trolley eye with a hook or a shackle.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -10°C - (+)50°C

Finish: Painted, yellow

Standard: EN 13157

Safety factor: 4:1

| Part Code | WLL ton | Beam width mm | Min. Radius Curve m | B mm | J mm | K mm | F mm | E mm | D mm | L mm | H mm | G mm | Weight kg |
|-----------|---------|---------------|---------------------|------|------|-------|------|------|------|------|------|------|-----------|
| SIVA05H | 0.5 | 55-220 | 0.5 | 285 | 198 | 158 | 12.5 | 40 | 3 | 55 | 80 | 25 | 5 |
| SIVA05HL | 0.5 | 55-305 | 0.5 | 385 | 198 | 158 | 12.5 | 40 | 3 | 55 | 80 | 25 | 5.4 |
| SIVA10H | 1 | 58-220 | 0.7 | 300 | 238 | 183 | 17 | 31 | 3 | 68 | 96 | 29 | 8.8 |
| SIVA10HL | 1 | 58-305 | 0.7 | 238 | - | 183 | 17 | 31 | 3 | 68 | 96 | 29 | 9.3 |
| SIVA20H | 2 | 66-220 | 0.9 | 300 | 277 | 208 | 20 | 31 | 3 | 80 | 110 | 36 | 14 |
| SIVA20HL | 2 | 66-305 | 0.9 | 405 | 277 | 208 | 20 | 31 | 3 | 80 | 110 | 36 | 14.8 |
| SIVA30H | 3 | 74-220 | 1.2 | 328 | 324 | 249 | 26 | 31 | 3 | 100 | 132 | 46 | 23 |
| SIVA30HL | 3 | 74-305 | 1.2 | 429 | 324 | 249 | 26 | 31 | ~3 | 100 | 132 | 46 | 24.1 |
| SIVA50H | 5 | 90-220 | 1 | 354 | 373 | 296.5 | 28 | 40 | 5 | 120 | 155 | 52 | 40 |
| SIVA50HL | 5 | 90-305 | 1 | 435 | 373 | 296.5 | 28 | 40 | ~5 | 120 | 155 | 52 | 41.1 |

Blueprint

